


RECORD OF SURVEY No. 31-61

IN THE UNINCORPORATED TERRITORY OF THE COUNTY OF MONO, STATE OF CALIFORNIA,
BEING SECTIONS 21, 22, 27-30, 35 & 36, TOGETHER WITH THE SOUTHERLY TOWNSHIP LINE
FROM SECTION 33 TO 36, TOWNSHIP 7 NORTH, RANGE 23 EAST, MOUNT DIABLO MERIDIAN

MONUMENT DESCRIPTIONS:

100200



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, 2 INCHES ABOVE THE TOP OF A MOUND OF STONES, 2 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN GREAT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.5 FEET NORTHERLY. FOUND ORIGINAL BEARING TREE:

BT1: A 26 INCH WHITE PINE, S11°E, 100.5 FEET

ALSO FOUND 1987 BEARING TREES:

BT2: A 24 INCH WHITE PINE, N39°E, 66.2 FEET

BT3: A 22 INCH LODGEPOLE PINE, S17°W, 101.8 FEET


BT4: A 14 INCH LODGEPOLE PINE, N64°W, 65.9 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED

100207

FOUND REMAINS OF ORIGINAL LINE TREE, A 53 INCH YELLOW PINE STUMP WITH NOTCHES, AND A 1987 BLM BEARING TREE SIGN, ON THE SOUTH SIDE, POSITIONED CENTER OF REMAINS AS BEST AS COULD BE DETERMINED, SET NOTHING

100207RM



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, 3 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN GOOD CONDITION, ADDED A MOUND OF STONES 2.5 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.0 FOOT NORTHERLY. MONUMENT IS N33°41'W, 8.69 FEET FROM THE APPROXIMATE CENTER OF THE STUMP (100207), AND 6.5 FEET FROM THE NORTHWESTERLY FACE OF THE STUMP

100240




FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, 4 INCHES ABOVE THE TOP OF A MOUND OF STONES, 4 FEET IN DIAMETER AND 10 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN GREAT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.6 FEET SOUTHERLY. FOUND ORIGINAL BEARING TREES:

BT1: A 14 INCH LODGEPOLE PINE, N33°E, 5.7 FEET

BT2: A 16 INCH LODGEPOLE PINE, S47°W, 6.2 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED

100300



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, 4 INCHES ABOVE THE TOP OF A MOUND OF STONES, 3.5 FEET IN DIAMETER AND 12 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN GREAT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.7 FEET SOUTHERLY. FOUND ORIGINAL BEARING TREES:

BT1: A DEAD 13 INCH WHITE PINE, S53°E, 116.2 FEET

BT2: THE EASTERLY 60 INCH FORK ON A FORKED WHITE PINE, N65°W, 142.2 FEET

FOUND 1986 BEARING TREES:


BT3: A 14 INCH WHITE PINE, N67°E, 144.0 FEET

BT4: A 24 INCH WHITE PINE, S28°E, 81.5 FEET

BT5: A 20 INCH WHITE PINE, S07°W, 116.6 FEET

ADDED, TO EACH LIVE TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED

140200



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, 4 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, ADDED A MOUND OF STONES TO 2.0 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.5 FEET SOUTHERLY. FOUND ORIGINAL BEARING TREE:

BT1: A 72 INCH JEFFREY PINE, S18°E, 29.3 FEET


FOUND 1987 BEARING TREES:

BT2: A 24 INCH JEFFREY PINE, N50°E, 82.5 FEET

BT3: A 10 INCH JUNIPER, S35°E, 10.9 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED

140240




SET A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A ¾ INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2½ INCH DIAMETER POST, 30 INCHES LONG, 26 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.5 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 2.0 FEET SOUTHWESTERLY. SET NEW BEARING TREES SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: A 22 INCH JEFFREY PINE, S59°E, 80.3 FEET

BT2: A 6 INCH JEFFREY PINE, S63°W, 49.9 FEET

MONUMENT DESCRIPTIONS:

140300



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A MOUND OF STONES, 4.0 FEET IN DIAMETER AND 10 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 2.5 FEET NORTHWESTERLY. FOUND ORIGINAL BEARING TREES:

BT1: A 34 INCH SAWED YELLOW PINE STUMP, N72°E, 41.3 FEET

BT2: A 26 INCH SAWED YELLOW PINE STUMP, S35°E, 23.0 FEET

FOUND 1986 BEARING TREES:


BT3: A 15 INCH WHITE FIR, S30°W, 14.2 FEET

BT4: A 14 INCH WHITE FIR, N29°W, 17.8 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. SET A NEW BEARING TREE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT5: A 16 INCH JEFFREY PINE, S79°E, 11.4 FEET

160220




SET A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A ¾ INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2½ INCH DIAMETER POST, 30 INCHES LONG, 26 INCHES IN THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 1.5 FEET SOUTHWESTERLY. SET NEW BEARING TREES SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: AN 18 INCH FIR, N89°W, 18.1 FEET

BT2: AN 18 INCH FIR, S12°E, 14.9 FEET

160240




SET A STANDARD US FOREST SERVICE ALUMINUM MONUMENT WITH A ¾ INCH DIAMETER ALUMINUM CAP, STAMPED AS SHOWN, ON A 2½ INCH DIAMETER POST, 30 INCHES LONG, 26 INCHES IN THE GROUND, ENCIRCLED BY A MOUND OF STONES, 2.0 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. PLACED A PLASTIC ENCASED MAGNET BENEATH THE MONUMENT. SET A U CHANNEL ALUMINUM POST WITH FOREST SERVICE 54-9 MONUMENT SIGN AND A FOREST SERVICE 54-2 BOUNDARY SIGN, 2.0 FEET SOUTHWESTERLY. SET NEW BEARING TREES SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT1: A 12 INCH TAMARACK, N71°E, 24.8 FEET

BT2: A 12 INCH FIR, N25°W, 27.7 FEET

200100




FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A MOUND OF STONES, 3.5 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET NORTHERLY. FOUND 1987 BEARING TREE:

BT1: A 30 INCH LODGEPOLE PINE, N06°E, 174.9 FEET

ADDED TO TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. SET A NEW BEARING TREE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT2: A 14 INCH LODGEPOLE PINE, S73°W, 94.5 FEET

200200



SEARCHED, FOUND NO EVIDENCE OF A CHISELED "X" PER THE 1987 BLM NOTES, ALSO FOUND DISCREPANCIES BETWEEN SAID NOTES AND THE ACTUAL RM (200200RM) CAP STAMPING, AS WELL AS WITH THE DIMENSIONS TO THE REFERENCE OBJECTS, SEE "HISTORY OF SURVEYS AND BOUNDARY DISCUSSION" ON PAGE 1. ESTABLISHED BY DOUBLE PROPORTION FROM 200100 TO THE SOUTH, 200240 TO THE NORTH, 140200 TO THE WEST, AND 300200 TO THE EAST. SET A STANDARD US FOREST SERVICE ¾ INCH DIAMETER ALUMINUM CAP WITH MAGNET, STAMPED AS SHOWN, DRILLED INTO THE TOP OF A 10 FOOT X 8 FOOT X 8 FOOT HIGH BOULDER. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 8.0 FEET EASTERLY. FOUND 1987 BEARING TREE:

BT1: A 28 INCH JUNIPER, N08°W, 119.8 FEET (RECORD WAS N06.5°W, 118.8 FEET)


ADDED TO TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. ALSO FOUND 1987 BEARING OBJECTS:

B01: A 4 FOOT X 6 FOOT X 8 FOOT HIGH BOULDER MARKED "BXO", N68°E, 78.1 FEET (RECORD WAS N70°E, 81.8 FEET)

B02: A 10 FOOT X 7 FOOT X 6 FOOT HIGH BOULDER MARKED "BXO", S02°W, 48.1 FEET (RECORD WAS S02.25°E, 48.5 FEET)

MONUMENT DESCRIPTIONS:

200200RM




FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A SMALL RING OF STONES. FOUND THE MONUMENT IN GOOD CONDITION, STRAIGHT AND SOLID, ADDED A MOUND OF STONES 2.0 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET EASTERLY. NO NEW OR EXISTING BEARING TREES. THIS MONUMENT IS N55°18'E, 46.26 FEET FROM THE TRUE CORNER (RECORD PER 1987 BLM NOTES WAS N61°22'E, 52.8 FEET). 200200CNAIL, DESCRIBED BELOW, IS S59°40'W, 49.45 FEET FROM THIS MONUMENT

200200CNAIL

FOUND A CONCRETE NAIL (C-NAIL), N84°36'W, 3.94 FEET FROM THE TRUE CORNER, 200200. THIS NAIL APPEARS TO HAVE BEEN SOME KIND OF TEMPORARY, OR WORKING POINT, FROM WHICH THE TRUE CORNER WAS LATER TO BE SET. THE EVIDENCE SUGGESTS THAT A SOUTHWEST BEARING, INSTEAD OF THE CORRECT SOUTHEAST BEARING, WAS USED DURING THE OFFICE CALCULATIONS TO DETERMINE THE BEARINGS AND DISTANCES TO THE REFERENCE MONUMENT AND BEARING OBJECTS

200220



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A MOUND OF STONES, 2.5 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES TO 3.5 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 2.0 FEET SOUTHWESTERLY. FOUND 1987 BEARING TREES:


BT1: A 12 INCH JUNIPER, S68°E, 35.8 FEET

BT2: AN 8 INCH WHITE FIR, N29°W, 6.2 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. SET A NEW BEARING TREE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT3: AN 8 INCH WHITE FIR, N15°E, 11.5 FEET

200240



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A MOUND OF STONES, 4.0 FEET IN DIAMETER AND 4 INCHES ABOVE THE GROUND. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES TO 4.0 FEET IN DIAMETER AND 8 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN, 1.0 FOOT WESTERLY. FOUND ORIGINAL BEARING TREE:


BT1: A 36 INCH YELLOW PINE, N19°E, 35.3 FEET

FOUND 1986 BEARING TREE:

BT2: A 14 INCH FIR, N81°W, 51.3 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED

200260



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A MOUND OF STONES, 2.5 FEET IN DIAMETER AND 6 INCHES ABOVE THE GROUND. ALSO FOUND AN ALUMINUM POST WITH A FOREST SERVICE 54-4 ATTENTION SIGN 3 FEET SOUTHERLY. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A 54-2 BOUNDARY SIGN, 2.5 FEET NORTHEASTERLY. FOUND 1987 BEARING TREES:


BT1: AN 18 INCH JEFFREY PINE, N01°E, 23.3 FEET

BT2: A 13 INCH JEFFREY PINE, S06°E, 21.9 FEET

ADDED, TO EACH TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. SET A NEW BEARING TREE SCRIBED "BT", WITH 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR CHAINING POINT AT CENTER RIGHT SIDE, AND FOREST SERVICE 54-3 BEARING TREE SIGN:

BT3: A 7 INCH FIR, N60°E, 5.6 FEET

200300



FOUND A 2½ INCH STAINLESS STEEL PIPE WITH A ¾ INCH BRASS CAP STAMPED AS SHOWN, ENCIRCLED BY A LOOSE MOUND OF STONES, 4.0 FEET IN DIAMETER. FOUND THE MONUMENT IN EXCELLENT CONDITION, STRAIGHT AND SOLID, REBUILT MOUND OF STONES TO 4.0 FEET IN DIAMETER AND 12 INCHES ABOVE THE GROUND. SET A U CHANNEL ALUMINUM POST WITH A FOREST SERVICE 54-9 MONUMENT SIGN AND A 54-2 BOUNDARY SIGN, 2.5 FEET NORTHEASTERLY. FOUND ORIGINAL BEARING TREES:

BT1: A 27 INCH FIR, S70°E, 9.7 FEET

BT2: A 38 INCH JEFFREY PINE, S18°W, 29.4 FEET

BT3: AN 11 INCH SAWED YELLOW PINE STUMP, N05°W, 28.9 FEET

FOUND 1986 BEARING TREES:

BT4: A 20 INCH JUNIPER, N60°E, 70.2 FEET

BT5: A 14 INCH FIR, N30°W, 58.1 FEET

ADDED, TO EACH LIVE TREE, A FOREST SERVICE 54-3 BEARING TREE SIGN AND A 6" MAG SPIKE AND "PLS 7172" STAINLESS STEEL WASHER FOR A CHAINING POINT AT CENTER RIGHT SIDE. NO NEW BEARING TREES ESTABLISHED